

Englefield STREET TREET TREET

KOHLER NEW ZEALAND LIMITED

133 DIANA DRIVE, GLENFIELD AUCKLAND 0627 PO BOX 100-146 N.S.M.C AUCKLAND NEW ZEALAND PHONE +64 9 980 6800

Kohler Drop-In Baths BPIR Declaration

Version: A (12/23)

Designated building product: Class 1

Declaration

Kohler New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name Kohler Drop-In Baths

Identifier Odeon / Patio / Regatta

Description

Drop-In Acrylic baths intended for personal bathing in residential & commercial applications.

Manufactured in vacuum formed white Sanitary Grade Acrylic, fully reinforced with fibreglass & a fully encapsulated particle board base. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.

Rectangular sizes: 1520x760, 1670x760, 1670x820. 1800x760, 1800x820

All sizes are nominal & specific availability varies according to the chosen range (identifier).

Scope of use

For interior installations in residential & commercial buildings.

Rectangular drop-baths can be installed to one, two (corner) or three (alcove) walls. All dropin baths can be hob mounted away from adjacent walls.

Kohler Acrylic Drop-In Baths cannot be installed as shower-over-baths (please refer to our specific Englefield shower-over-bath products for this purpose).

Waste / drain holes are located either centrally or at one end & are compatible with standard DN40 waste outlets. These baths do not have an integrated overflow. Consider other options in overall bathroom design to contribute to E3 Internal moisture compliance. Hot water must be supplied to this sanitary fixture via adjacent tapware.

Conditions of use

The bath must be installed in accordance with our supplied instructions be installed level on all top edges. The rim and the base of the bath must be fully supported. Do not hang the bath by the rim. Plan for access panels to simplify further access to waste, overflow and tapware.

The tapware, waste & any overflow must be installed by a Registered Plumber. The maximum temperature of water at the bath outlet is 50 degrees Celsius.

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2

Contributions to compliance

B2.3.1(c): Per B2/AS1, Durability Requirements of Nominated Building Elements

for Plumbing Fixtures, the Kohler Acrylic Drop-In Baths have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. Kohler Acrylic Drop-In Baths are designed & manufactured to AS/NZS 2023: 1995 (Baths for ablutionary purposes).

E3/AS1 3.2.2: Where Kohler Acrylic Drop-In Baths abut impervious wall linings (refer

Scope of Use), the joint between fixture and lining shall be sealed to prevent water penetration to concealed spaces or behind linings. Odeon & Regatta drop-in baths feature a 12.5mm high continuous

moulded upstand for ease of sealing.

F2.3.1: No materials used in the construction of Kohler Acrylic Drop-In Baths

give rise to harmful concentrations at the surface of the material where

the material is exposed, or in the atmosphere of any space.

G1.3.2: The Sanitary Grade Acrylic used features a high gloss surface for ease

of cleaning.

G1/AS1 2.6.1: Kohler Acrylic Drop-In Baths are designed & manufactured to AS/NZS

2023: 1995 (Baths for ablutionary purposes).

G12.3.5: Kohler Acrylic Drop-In Baths must be provided with hot water to satisfy

the intended usage of personal bathing (note - tapware not included).

Supporting documentation

The following additional documentation supports the above statements:

Installation instructions - Bath	<u>V080008-A04-L</u>
Warranty statement	<u>1173921-A</u>
Care & maintenance guide	Homeowners Care Guide

For further information supporting Kohler Drop-In Baths claims refer to our website.

Contact details

Manufacture location	China
Manufacturer name(s)	Shanghai Kohler Co. Ltd.
Legal and trading name of importer	Kohler New Zealand Limited
Importer address for service	133 Diana Drive Auckland 0627
Importer website(s)	kohler.co.nz
Importer email	customerservicesnz@kohler.com
Importer phone number	099806800
Importer NZBN	9429037167615